APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/662,034	09/12/2003	Paul J. Mantey	200309970-1	9298

22879   7590   03/25/2008
HEWLETT PACKARD COMPANY
P O BOX 272400, 3404 E. HARMONY ROAD
INTELLECTUAL PROPERTY ADMINISTRATION
FORT COLLINS, CO 80527-2400

EXAMINER
SPITTLE, MATTHEW D

ART UNIT	PAPER NUMBER
2111	

NOTIFICATION DATE	DELIVERY MODE
03/25/2008	ELECTRONIC

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

JERRY.SHORMA@HP.COM
mkraft@hp.com
ipa.mail@hp.com

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.
- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

1)☒ Responsive to communication(s) filed on *21 December 2007*.
2a)☐ This action is **FINAL**.　　　2b)☒ This action is non-final.
3)☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

4)☒ Claim(s) *1-13 and 42-44* is/are pending in the application.
　　4a) Of the above claim(s) _____ is/are withdrawn from consideration.
5)☐ Claim(s) _____ is/are allowed.
6)☒ Claim(s) *1-13, 42-44* is/are rejected.
7)☐ Claim(s) _____ is/are objected to.
8)☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

9)☐ The specification is objected to by the Examiner.
10)☐ The drawing(s) filed on _____ is/are: a)☐ accepted or b)☐ objected to by the Examiner.
　　Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
　　Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

12)☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
　　a)☐ All　b)☐ Some * c)☐ None of:
　　　1.☐ Certified copies of the priority documents have been received.
　　　2.☐ Certified copies of the priority documents have been received in Application No. _____.
　　　3.☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
　　* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

1)☒ Notice of References Cited (PTO-892)
2)☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
3)☐ Information Disclosure Statement(s) (PTO/SB/08)
　　Paper No(s)/Mail Date _____.

4)☐ Interview Summary (PTO-413)
　　Paper No(s)/Mail Date. _____.
5)☐ Notice of Informal Patent Application
6)☐ Other: _____.

DETAILED ACTION

Claims 1 – 13, and 42 – 44 have been examined.

Claim Rejections - 35 USC § 103

5   The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all

obviousness rejections set forth in this Office action:

> (a) A patent may not be obtained though the invention is not identically disclosed or described as set
> forth in section 102 of this title, if the differences between the subject matter sought to be patented and
> the prior art are such that the subject matter as a whole would have been obvious at the time the
> 10   invention was made to a person having ordinary skill in the art to which said subject matter pertains.
> Patentability shall not be negatived by the manner in which the invention was made.

The factual inquiries set forth in *Graham* **v.** *John Deere Co.*, 383 U.S. 1, 148

USPQ 459 (1966), that are applied for establishing a background for determining

15   obviousness under 35 U.S.C. 103(a) are summarized as follows:

1.   Determining the scope and contents of the prior art.
2.   Ascertaining the differences between the prior art and the claims at issue.
3.   Resolving the level of ordinary skill in the pertinent art.
4.   Considering objective evidence present in the application indicating
20   obviousness or nonobviousness.

Claims 1 – 4 and 12 are rejected under 35 U.S.C. 103(a) as being unpatentable

over Johnson et al. (U.S. 6,122,758) in view of Yik et al. (U.S. Pub. 2003/0226050).

Regarding claim 1, Johnson et al. describe a computer system comprising:

25   A system bus implemented in accordance with an Inter-IC bus specification

(Figure 4, 7, item 310; column 7, lines 10 – 12);

A bus controller coupled to the system bus (where a bus controller may be

interpreted as a system interface processor; column 11, lines 31 – 36, 61 - 65) and to

an internal bus (Fig. 4, 7, item 226);

30   A send machine (Fig. 7, item 707) and a FIFO buffer coupled to the send

machine (Fig. 7, 516), however Johnson et al. fails to teach the send machine and FIFO

buffer connected as recited in the claim.

Yik et al. teach a bridge circuit (Fig. 1, 100) which could be implemented in a

system such as that of Johnson et al. for the purpose of allowing components to operate

35   at different clock rates, and for power saving purposes (par. 5). This circuit could be

implemented in Johnson et al., for example, in the location of items 514 and 516 in

Figure 7 to allow the system interface processor (312) and host processor (200) to

operate at different clock rates. Thus, the combination of Johnson et al. and Yik et al.

teach a send machine (Yik et al.: 150) coupled between a host processor (Johnson:

40   200) and the bus controller (Johnson: 312) over a second internal bus (Yik et al. 156,

162); and a first first-in first-out (FIFO) buffer (Yik et al.: 154) coupled to the send

machine (Yik et al.: 150), the first FIFO further coupled in parallel with the send machine

(as shown in Yik et al., Fig. 1) between the host processor (Johnson: 200) and the bus

controller (Johnson: 312) over the first internal bus (Johnson: 226) but not over the

45   system bus (Johnson: 310).

Therefore, it would have been obvious to one of ordinary skill in this art at the

time of invention by Applicant to incorporate the bridge circuit as taught by Yik et al. into

the system of Johnson et al. for the purpose of allowing different components on the

bus to correctly operate at different clock rates and to save power (par. 5). This would

50   have been obvious since Yik et al. teach that it is advantageous to reduce the amount of

power required to process data, thereby reducing the amount of heat generated, thus

prolonging the life of the hardware (par. 3).

55   Regarding claim 2, Yik et al. teach the additional limitation wherein the first FIFO

buffer comprises means for receiving a plurality of bytes from the host processor without

interrupting the host processor (par 21).

       Regarding claim 3, Yik et al. teach the additional limitation wherein:

       The first FIFO buffer comprises means for receiving a plurality of bytes from the

60   host processor (par. 21);

       The send machine comprises means for transmitting the plurality of bytes over

the system bus without interrupting the host processor (par. 21).

       Regarding claim 4, Yik et al. teach the additional limitation comprising:

65   A receive machine (Fig. 1, 136) coupled between the host processor and the bus

controller;

       A second FIFO buffer coupled to the receive machine and coupled between the

host processor and the bus controller (Fig. 1, 142).

70   Regarding claim 12, Johnson et al. describe a computer system comprising:

       A system bus implemented in accordance with an Inter-IC bus specification

(Figure 4, 7, item 310; column 7, lines 10 – 12);

A bus controller coupled to the system bus (where a bus controller may be interpreted as a system interface processor; column 11, lines 31 – 36, 61 - 65) and to

75   an internal bus (Fig. 4, 7, item 226);

A send machine (Fig. 7, item 707) and a FIFO buffer coupled to the send machine (Fig. 7, 516), however Johnson et al. fails to teach the send machine and FIFO buffer connected as recited in the claim.

Yik et al. teach a bridge circuit (Fig. 1, 100) which could be implemented in a

80   system such as that of Johnson et al. for the purpose of allowing components to operate at different clock rates, and for power saving purposes (par. 5). This circuit could be implemented in Johnson et al., for example, in the location of items 514 and 516 in Figure 7 to allow the system interface processor (312) and host processor (200) to operate at different clock rates. Thus, the combination of Johnson et al. and Yik et al.

85   teach a send machine (Yik et al.: 150) coupled between a host processor (Johnson: 200) and the bus controller (Johnson: 312) over a second internal bus (Yik et al. 156, 162); and a first first-in first-out (FIFO) buffer (Yik et al.: 154) coupled to the send machine (Yik et al.: 150), the first FIFO further coupled in parallel with the send machine (as shown in Yik et al., Fig. 1) between the host processor (Johnson: 200) and the bus

90   controller (Johnson: 312) over the first internal bus (Johnson: 226) but not over the system bus (Johnson: 310).

Additionally, Yik et al. teaches a receive machine (136) coupled between the host processor and the bus controller, the receive machine comprising means for receiving the plurality of bytes over the system bus without interrupting the host processor (par.

95   21); and a second FIFO buffer coupled to the receive machine and coupled between the

host processor and the bus controller (142) over the **third** internal bus (146, 140, 106),

the second FIFO not being coupled to the receive machine over the second internal bus

(as shown in Fig. 1) but not over the system bus (as shown in Fig. 1), the second FIFO

buffer comprising means for receiving a plurality of bytes from the bus controller without

100   interrupting the host processor (par. 18).

Therefore, it would have been obvious to one of ordinary skill in this art at the

time of invention by Applicant to incorporate the bridge circuit as taught by Yik et al. into

the system of Johnson et al. for the purpose of allowing different components on the

bus to correctly operate at different clock rates and to save power (par. 5). This would

105   have been obvious since Yik et al. teach that it is advantageous to reduce the amount of

power required to process data, thereby reducing the amount of heat generated, thus

prolonging the life of the hardware (par. 3).

*   *   *

110

Claim 5 is rejected under 35 U.S.C. 103(a) as being unpatentable over Johnson

et al. (U.S. 6,122,758) in view of Yik et al. (U.S. Pub. 2003/0226050) and Yoshida (U.S.

5,928,372).

Johnson et al. fail to teach wherein the receive machine comprises checksum

115   generation means for generating a message checksum for a message while the

message is being received by the bus controller over the system bus.

Yoshida teaches a checksum generation means for generating a message

checksum for a message while the message is being received by the bus controller over

the system bus (where checksum generation means may be interpreted as data check

120   code generation circuits; column 11, lines 14 – 24).

It would have been obvious to one or ordinary skill in this art at the time of

invention by applicant to combine the checksum generation means of Yoshida with the

system of Johnson et al. and Yik et al. in order to provide for a means of verifying the

data transmitted across the system bus. This would have been obvious since error-free

125   data is critical to the correct operation of a digital system.

*   *   *

Claims 6 – 8 are rejected under 35 U.S.C. 103(a) as being unpatentable over

130   Johnson et al. (U.S. 6,122,758) in view of Yik et al. (U.S. Pub. 2003/0226050) and

Feeney et al. (U.S. 6,072,781).

With regard to claim 6, Johnson et al. describe the computer system of claim 1,

further comprising:

Means for receiving a message from the host processor (Figure 7, items 516,

135   707; column 12, lines 26 – 32);

Means for attempting to send the message over the system bus to a target

device (column 15, lines 15 – 36 give an example of how a message is sent over the

system bus to a target device (microcontroller)).

Means for determining whether the message was received without errors by the

140   target device (column 15, lines 62 – 64).

Johnson et al. and Yik et al. fail to describe retry means for attempting again to

send the message over the communication bus to the target device if it is determined

that the message was not received without errors by the target.

Feeney et al. teach retry means for attempting again to send the message over

145   the system bus to the target device without interrupting the host processor if it is

determined that the message was not received without errors by the target device

(column 16, lines 36 – 49 describe retrying messages that failed to send; column 16,

lines 36 – 49 describe retrying a message without involving the processor).

It would have been obvious to one of ordinary skill in this art at the time of

150   invention by applicant to incorporate the means of retrying failed messages as taught by

Feeney et al. into the computer system of Johnson et al. and Yik et al. for the purpose

of ensuring the delivery of messages on the communication bus.

With regard to claim 7, Feeney et al. teach the additional limitation wherein the

155   retry means comprises means for attempting again to send the message over the

system bus to the target device without interrupting the host processor if it is determined

that the message was not received without errors by the target device (column 16, lines

36 – 49 describe retrying a message without involving the processor).

160   With regard to claim 8, Feeney et al. teach the additional limitation wherein the

retry means comprises means for attempting again to send the message over the

system bus to the target device without obtaining the message again from the host

processor if it is determined that the message was not received without errors by the

target device (column 16, lines 36 – 49 describe storing the message in a FIFO in order

165   to allow the processor to move onto other tasks).

*   *   *

            Claim 9 is rejected under 35 U.S.C. 103(a) as being unpatentable over Johnson

170   et al. (U.S. 6,122,758) in view of Yik et al. (U.S. Pub. 2003/0226050) and Cao et al.

(U.S. 5,230,044).

            Johnson et al. and Yik et al. fail to teach a busfree count means for storing a

busfree count associated with the computer system, a busfree timer for use by the

computer system to wait an amount of time specified by the busfree count prior to

175   attempting to access the system bus after the system bus becomes available for use,

and a fair arbitration block coupled between the host processor and the bus controller,

the fair arbitration block comprising arbitration means for modifying the busfree count

according to a priority signal to produce an arbitrated busfree count signal.

            Cao et al. teach:

180   A busfree count means for storing a busfree count (where a busfree count may

be interpreted as an arbitration count number; column 4, lines 42 – 50);

A busfree timer for use by the computer system to wait an amount of time

specified by the busfree count prior to attempting to access the system bus after the

system bus becomes available for use (where a busfree timer may be interpreted as a

185   "quiet slot" counter; column 4, lines 51 – 60);

A fair arbitration block comprising arbitration means for modifying the busfree

count according to a priority signal to produce an arbitrated busfree count signal (where

a busfree count may be interpreted as an arbitration count number; column 5, lines 59 –

64).

190   It would have been obvious to one of ordinary skill in this art at the time of

invention by applicant to incorporate the busfree count and busfree timer as taught by

Cao et al. into the system of Johnson et al. and Yik et al. for the purpose of providing

arbitration amongst devices on the system bus. This would have been obvious since

Cao et al. teach that their invention provides for more efficient use of bus bandwidth

195   (column 10, lines 25 – 59), along with permitting data communication with a very small

probability of data collisions (column 4, lines 32 – 34).

*   *   *

200   Claims 10 and 11 are rejected under 35 U.S.C. 103(a) as being unpatentable

over Johnson et al. (U.S. 6,122,758) in view of Yik et al. (U.S. Pub. 2003/0226050) and

Webb et al. (U.S.4,577,060).

With regard to claim 10, Johnson et al. and Yik et al. fail to teach a byte timer coupled between the bus controller and the host processor.

205   Webb et al. teach a byte timer (where a byte timer may be interpreted as a no-response timer; column 13, lines 49 - 60).

It would have been obvious to one of ordinary skill in this art at the time of invention by applicant to include the byte timer as taught by Webb et al. into the system of Johnson et al. and Yik et al.. This would have been obvious in order to provide a

210   method of ensuring that a communication link (or bus) is operating properly, and prevent the system from wasting time sending messages to processors/terminals that are not responsive (column 14, lines 11 – 19).

With regard to claim 11, Webb et al. teach the additional limitation wherein the

215   byte timer (interpreted as a no-response timer) comprises means for determining whether the host processor has failed and means for generating a signal indicating whether the host processor has failed (where a host processor may be interpreted as a terminal; where generating a signal indicating the processor has failed may be interpreted as marking a terminal as being "offline" or "down"; column 13, line 49 –

220   column 14, line 30).

*   *   *

Claim 13 is rejected under 35 U.S.C. 103(a) as being unpatentable over Johnson

225   et al. in view of Yik et al., Feeney et al., Cao et al., and further in view of Webb et al.

Johnson et al. teach a computer system of claim 12 further comprising:

Means for receiving a message from the host processor (Figure 7, items 516,

707; column 12, lines 26 – 32);

Means for attempting to send the message over the system bus to a target

230   device (column 15, lines 15 – 36 give an example of how a message is sent over the

system bus to a target device (microcontroller)).

Means for determining whether the message was received without errors by the

target device (column 15, lines 62 – 64).

Johnson et al. and Yik et al. fail to describe a retry means, a busfree count

235   means, a busfree count timer, a fair arbitration block, and a byte timer.

Feeney et al. teach retry means for attempting again to send the message over

the system bus to the target device without interrupting the host processor if it is

determined that the message was not received without errors by the target device

(column 16, lines 36 – 49 describe retrying messages that failed to send; column 16,

240   lines 36 – 49 describe retrying a message without involving the processor).

It would have been obvious to one of ordinary skill in this art at the time of

invention by applicant to incorporate the means of retrying failed messages as taught by

Feeney et al. into the computer system of Liu et al for the purpose of ensuring the

delivery of messages on the communication bus.

245   Cao et al. teach:

A busfree count means for storing a busfree count (where a busfree count may

be interpreted as an arbitration count number; column 4, lines 42 – 50);

A busfree timer for use by the computer system to wait an amount of time

specified by the busfree count prior to attempting to access the system bus after the

250   system bus becomes available for use (where a busfree timer may be interpreted as a

"quiet slot" counter; column 4, lines 51 – 60);

A fair arbitration block comprising arbitration means for modifying the busfree

count according to a priority signal to produce an arbitrated busfree count signal (where

a busfree count may be interpreted as an arbitration count number; column 5, lines 59 –

255   64).

It would have been obvious to one of ordinary skill in this art at the time of

invention by applicant to incorporate the busfree count and busfree timer as taught by

Cao et al. into the system of Johnson et al., Yik et al., and Feeney et al, for the purpose

of providing arbitration amongst devices on the system bus. This would have been

260   obvious since Cao et al. teach that their invention provides for more efficient use of bus

bandwidth (column 10, lines 25 – 59), along with permitting data communication with a

very small probability of data collisions (column 4, lines 32 – 34).

Webb et al. teach a byte timer comprising means for determining whether the

host processor has failed and means for generating a signal indicating whether the host

265   processor has failed (where a byte timer may be interpreted as a no-response timer;

column 13, lines 49 – 60; where a host processor may be interpreted as a terminal;

where generating a signal indicating the processor has failed may be interpreted as

marking a terminal as being "offline or "down"; column 13, line 49 – column 14, line 30).

It would have been obvious to one of ordinary skill in this art at the time of

270   invention by applicant to include the byte timer as taught by Webb et al. into the system

of Johnson et al., Feeney et al., and Cao et al. This would have been obvious in order

to provide a method of ensuring that a communication link (or bus) is operating properly,

and prevent the system from wasting time sending messages to processors/terminals

that are not responsive (column 14, lines 11 – 19).

275

*   *   *

Claim 42 is rejected under 35 U.S.C. 103(a) as being unpatentable over Johnson

et al. in view of Yik et al., Feeney et al., Cao et al., and Webb et al.

280   Regarding claim 42, Johnson et al. teach a computer system comprising:

A system bus implemented in accordance with an Inter-IC bus specification

(Figure 4, 7, item 310; column 7, lines 10 – 12);

A bus controller coupled to the system bus (where a bus controller may be

interpreted as a system interface processor; column 11, lines 31 – 36, 61 - 65) and to

285   an internal bus (Fig. 4, 7, item 226);

A send machine (Fig. 7, item 707) and a FIFO buffer coupled to the send

machine (Fig. 7, 516), however Johnson et al. fails to teach the send machine and FIFO

buffer connected as recited in the claim.

Yik et al. teach a bridge circuit (Fig. 1, 100) which could be implemented in a

290   system such as that of Johnson et al. for the purpose of allowing components to operate

at different clock rates, and for power saving purposes (par. 5). This circuit could be

implemented in Johnson et al., for example, in the location of items 514 and 516 in

Figure 7 to allow the system interface processor (312) and host processor (200) to

operate at different clock rates. Thus, the combination of Johnson et al. and Yik et al.

295   teach a send machine (Yik et al.: 150) coupled between a host processor (Johnson:

200) and the bus controller (Johnson: 312) over a second internal bus (Yik et al. 156,

162); and a first first-in first-out (FIFO) buffer (Yik et al.: 154) coupled to the send

machine (Yik et al.: 150), the first FIFO further coupled in parallel with the send machine

(as shown in Yik et al., Fig. 1) between the host processor (Johnson: 200) and the bus

300   controller (Johnson: 312) over the first internal bus (Johnson: 226) but not over the

system bus (Johnson: 310).

Additionally, Yik et al. teaches a receive machine (136) coupled between the host

processor and the bus controller, the receive machine comprising means for receiving

the plurality of bytes over the system bus without interrupting the host processor (par.

305   18); and a second FIFO buffer coupled to the receive machine and coupled between the

host processor and the bus controller (142) over the **third** internal bus (146, 140, 106),

the second FIFO not being coupled to the receive machine over the second internal bus

(as shown in Fig. 1) but not over the system bus (as shown in Fig. 1), the second FIFO

buffer comprising means for receiving a plurality of bytes from the bus controller without

310   interrupting the host processor (par. 18).

Therefore, it would have been obvious to one of ordinary skill in this art at the time of invention by Applicant to incorporate the bridge circuit as taught by Yik et al. into the system of Johnson et al. for the purpose of allowing different components on the bus to correctly operate at different clock rates and to save power (par. 5). This would

315   have been obvious since Yik et al. teach that it is advantageous to reduce the amount of power required to process data, thereby reducing the amount of heat generated, thus prolonging the life of the hardware (par. 3).

Johnson et al. additionally teaches means for receiving a message from the host processor (Figure 7, items 516, 707; column 12, lines 26 – 32);

320   Means for attempting to send the message over the system bus to a target device (column 15, lines 15 – 36 give an example of how a message is sent over the system bus to a target device (microcontroller)).

Means for determining whether the message was received without errors by the target device (column 15, lines 62 – 64).

325   Johnson et al. and Yik et al. fail to describe a retry means, a busfree count means, a busfree count timer, a fair arbitration block, and a byte timer.

Feeney et al. teach retry means for attempting again to send the message over the system bus to the target device without interrupting the host processor if it is determined that the message was not received without errors by the target device

330   (column 16, lines 36 – 49 describe retrying messages that failed to send; column 16, lines 36 – 49 describe retrying a message without involving the processor).

It would have been obvious to one of ordinary skill in this art at the time of

invention by applicant to incorporate the means of retrying failed messages as taught by

Feeney et al. into the computer system of Johnson et al. for the purpose of ensuring the

335   delivery of messages on the communication bus.

Cao et al. teach:

A busfree count means for storing a busfree count (where a busfree count may

be interpreted as an arbitration count number; column 4, lines 42 – 50);

A busfree timer for use by the computer system to wait an amount of time

340   specified by the busfree count prior to attempting to access the system bus after the

system bus becomes available for use (where a busfree timer may be interpreted as a

"quiet slot" counter; column 4, lines 51 – 60);

A fair arbitration block comprising arbitration means for modifying the busfree

count according to a priority signal to produce an arbitrated busfree count signal (where

345   a busfree count may be interpreted as an arbitration count number; column 5, lines 59 –

64).

It would have been obvious to one of ordinary skill in this art at the time of

invention by applicant to incorporate the busfree count and busfree timer as taught by

Cao et al. into the system of Johnson et al. and Yik et al. for the purpose of providing

350   arbitration amongst devices on the system bus. This would have been obvious since

Cao et al. teach that their invention provides for more efficient use of bus bandwidth

(column 10, lines 25 – 59), along with permitting data communication with a very small

probability of data collisions (column 4, lines 32 – 34).

Webb et al. teach a byte timer comprising means for determining whether the

355 host processor has failed and means for generating a signal indicating whether the host

processor has failed (where a byte timer may be interpreted as a no-response timer;

column 13, lines 49 – 60; where a host processor may be interpreted as a terminal;

where generating a signal indicating the processor has failed may be interpreted as

marking a terminal as being "offline or "down"; column 13, line 49 – column 14, line 30).

360 It would have been obvious to one of ordinary skill in this art at the time of

invention by applicant to include the byte timer as taught by Webb et al. into the system

of Johnson et al. and Yik et al.. This would have been obvious in order to provide a

method of ensuring that a communication link (or bus) is operating properly, and

prevent the system from wasting time sending messages to processors/terminals that

365 are not responsive (column 14, lines 11 – 19).

*   *   *

Claim 43 is rejected under 35 U.S.C. 103(a) as being unpatentable over Johnson

370 et al. (U.S. 6,122,758) in view of Yik et al. (U.S. Pub. 2003/0226050) and Yoshida (U.S.

5,928,372).

Johnson et al. and Yik et al. fail to teach wherein the receive machine comprises

checksum generation means for generating a message checksum for a message while

the message is being received by the bus controller over the system bus.

375   Yoshida teaches a checksum generation means for generating a message

checksum for a message while the message is being received by the bus controller over

the system bus (where checksum generation means may be interpreted as data check

code generation circuits; column 11, lines 14 – 24).

            It would have been obvious to one or ordinary skill in this art at the time of

380   invention by applicant to combine the checksum generation means of Yoshida with the

system of Johnson et al. in order to provide for a means of verifying the data transmitted

across the system bus. This would have been obvious since error-free data is critical to

the correct operation of a digital system.

385   *   *   *

            Claim 44 is rejected under 35 U.S.C. 103(a) as being unpatentable over Johnson

et al. in view of Yik et al. and Cao et al.

            Regarding claim 44, Johnson et al. teach a device for use in a computer system

390   including a system bus (Figure 4, 7, item 310; column 7, lines 10 - 12) and a bus

controller coupled to the system bus (where a bus controller may be interpreted as a

system interface processor; column 11, lines 31 – 36, 61 - 65).

            A send machine (Fig. 7, item 707) and a FIFO buffer coupled to the send

machine (Fig. 7, 516), however Johnson et al. fails to teach the send machine and FIFO

395   buffer connected as recited in the claim, as well as the first and second internal buses.

Yik et al. teach a bridge circuit (Fig. 1, 100) which could be implemented in a

system such as that of Johnson et al. for the purpose of allowing components to operate

at different clock rates, and for power saving purposes (par. 5). This circuit could be

implemented in Johnson et al., for example, in the location of items 514 and 516 in

400   Figure 7 to allow the system interface processor (312) and host processor (200) to

operate at different clock rates. Thus, the combination of Johnson et al. and Yik et al.

teach a send machine (Yik et al.: 150) coupled between a host processor (Johnson:

200) and the bus controller (Johnson: 312) over a second internal bus (Yik et al. 156,

162); and a first first-in first-out (FIFO) buffer (Yik et al.: 154) coupled to the send

405   machine (Yik et al.: 150), the first FIFO further coupled in parallel with the send machine

(as shown in Yik et al., Fig. 1) between the host processor (Johnson: 200) and the bus

controller (Johnson: 312) over the first internal bus (Johnson: 226) but not over the

system bus (Johnson: 310).

Additionally, Yik et al. teaches a receive machine (136) coupled between the host

410   processor and the bus controller, the receive machine comprising means for receiving

the plurality of bytes over the system bus without interrupting the host processor (par.

21); and a second FIFO buffer coupled to the receive machine and coupled between the

host processor and the bus controller (142) over the **third** internal bus (146, 140, 106),

the second FIFO not being coupled to the receive machine over the second internal bus

415   (as shown in Fig. 1) but not over the system bus (as shown in Fig. 1), the second FIFO

buffer comprising means for receiving a plurality of bytes from the bus controller without

interrupting the host processor (par. 18).

Therefore, it would have been obvious to one of ordinary skill in this art at the

time of invention by Applicant to incorporate the bridge circuit as taught by Yik et al. into

420   the system of Johnson et al. for the purpose of allowing different components on the

bus to correctly operate at different clock rates and to save power (par. 5). This would

have been obvious since Yik et al. teach that it is advantageous to reduce the amount of

power required to process data, thereby reducing the amount of heat generated, thus

prolonging the life of the hardware (par. 3).

425   Johnson et al. and Yik et al. fail to describe a busfree count means, a busfree

timer, and a fair arbitration block.

Cao et al. teach:

A busfree count means for storing a busfree count (where a busfree count may

be interpreted as an arbitration count number; column 4, lines 42 – 50);

430   A busfree timer for use by the computer system to wait an amount of time

specified by the busfree count prior to attempting to access the system bus after the

system bus becomes available for use (where a busfree timer may be interpreted as a

"quiet slot" counter; column 4, lines 51 – 60);

A fair arbitration block comprising arbitration means for modifying the busfree

435   count according to a priority signal to produce an arbitrated busfree count signal (where

a busfree count may be interpreted as an arbitration count number; column 5, lines 59 –

64).

It would have been obvious to one of ordinary skill in this art at the time of

invention by applicant to incorporate the busfree count and busfree timer as taught by

440   Cao et al. into the system of Johnson et al. and Yik et al. for the purpose of providing

arbitration amongst devices on the system bus. This would have been obvious since

Cao et al. teach that their invention provides for more efficient use of bus bandwidth

(column 10, lines 25 – 59), along with permitting data communication with a very small

probability of data collisions (column 4, lines 32 – 34).

445

Response to Arguments

Applicant's arguments, filed 11/28/2007, with respect to the rejection(s) of

claim(s) 1 – 13, and 42 – 44 under 35 USC 103 have been fully considered and are

450   persuasive. Therefore, the rejection has been withdrawn. However, upon further

consideration, a new ground(s) of rejection is made in view of Yik et al. (U.S. Pub.

2003/0226050).

Yik et al. teach a bridge circuit (Fig. 1, 100) which could be implemented in a

system such as that of Johnson et al. for the purpose of allowing components to operate

455   at different clock rates, and for power saving purposes (par. 5). This circuit could be

implemented in Johnson et al., for example, in the location of items 514 and 516 in

Figure 7 to allow the system interface processor (312) and host processor (200) to

operate at different clock rates. Thus, the combination of Johnson et al. and Yik et al.

teach a send machine (Yik et al.: 150) coupled between a host processor (Johnson:

460   200) and the bus controller (Johnson: 312) over a second internal bus (Yik et al. 156,

162); and a first first-in first-out (FIFO) buffer (Yik et al.: 154) coupled to the send

machine (Yik et al.: 150), the first FIFO further coupled in parallel with the send machine

(as shown in Yik et al., Fig. 1) between the host processor (Johnson: 200) and the bus

controller (Johnson: 312) over the first internal bus (Johnson: 226) but not over the

465   system bus (Johnson: 310).

Additionally, Yik et al. teaches a receive machine (136) coupled between the host

processor and the bus controller, the receive machine comprising means for receiving

the plurality of bytes over the system bus without interrupting the host processor (par.

18); and a second FIFO buffer coupled to the receive machine and coupled between the

470   host processor and the bus controller (142) over the **third** internal bus (146, 140, 106),

the second FIFO not being coupled to the receive machine over the second internal bus

(as shown in Fig. 1) but not over the system bus (as shown in Fig. 1), the second FIFO

buffer comprising means for receiving a plurality of bytes from the bus controller without

interrupting the host processor (par. 18).

475   Therefore, the Examiner cannot allow the claims.

Conclusion

The prior art made of record and not relied upon is considered pertinent to

applicant's disclosure.

480   Any inquiry concerning this communication or earlier system from the examiner

should be directed to MATTHEW D. SPITTLE whose telephone number is (571)272-

2467. The examiner can normally be reached on Monday - Friday, 9 - 5:30.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's

supervisor, Mark Rinehart can be reached on 571-272-3632. The fax phone number for

485   the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the

Patent Application Information Retrieval (PAIR) system. Status information for

published applications may be obtained from either Private PAIR or Public PAIR.

Status information for unpublished applications is available through Private PAIR only.

490   For more information about the PAIR system, see http://pair-direct.uspto.gov. Should

you have questions on access to the Private PAIR system, contact the Electronic

Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a

USPTO Customer Service Representative or access to the automated information

system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

495

/M. D. S./
Examiner, Art Unit 2111

/Mark Rinehart/
500   Supervisory Patent Examiner, Art Unit 2111